

540/70R30 159D TRACTOR KING SB TL

Revolutionary from surface to core

| | |
|--------------------------|----------------|
| PRODUCT CODE | T445677 |
| TIRE CLASSIFICATION CODE | R-1 |
| APPLICATION | Tractor |
| LI / SPEED SYMBOL | 159D |
| RIM RECOMMENDED | DW18L |
| RIM PERMITTED | DW16L, TW18L |
| TYPE APPROVAL | E8 106R-001177 |



LOAD CAPACITY FOR TRACTOR, KG

Tractor

| Pressure (kPa) | Speed (km/h) | | | | | | | | | | | | |
|----------------|--------------|------|------|------|------|------|------|------|------|------|------|------|------|
| | 5 | 10 | 15 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 |
| 80 | 3400 | 3000 | 2680 | 2460 | 2370 | 2300 | 2240 | 2190 | 2140 | 2100 | 2060 | 2030 | 2000 |
| 120 | 4380 | 3865 | 3450 | 3165 | 3050 | 2960 | 2885 | 2820 | 2755 | 2705 | 2650 | 2615 | 2575 |
| 160 | 5355 | 4725 | 4220 | 3875 | 3735 | 3625 | 3530 | 3450 | 3370 | 3310 | 3245 | 3195 | 3150 |
| 200 | 5865 | 5175 | 4625 | 4245 | 4090 | 3970 | 3865 | 3780 | 3690 | 3625 | 3555 | 3500 | 3450 |
| 240 | 6205 | 5475 | 4890 | 4490 | 4325 | 4200 | 4090 | 3995 | 3905 | 3835 | 3760 | 3705 | 3650 |
| 280 | 6800 | 6000 | 5360 | 4920 | 4740 | 4600 | 4480 | 4380 | 4280 | 4200 | 4120 | 4060 | 4000 |
| 320 | 7440 | 6565 | 5865 | 5380 | 5185 | 5030 | 4900 | 4790 | 4680 | 4595 | 4505 | 4440 | 4375 |

TIRE DIMENSIONS

| | New tire | Max. in service |
|-------------------------|----------|-----------------|
| OVERALL DIAMETER | 1506 mm | 1548 mm |
| TIRE WIDTH | 543 mm | 567 mm |
| PATTERN DEPTH | 50 mm | |
| MAX. INFLATION PRESSURE | 400 kPa | |

| | |
|-------------------------------|--|
| STATIC LOADED RADIUS | 693 mm @ 4375 kg / 320 kPa |
| DYNAMIC ROLLING CIRCUMFERENCE | 4539 mm @ 4375 kg / 320 kPa |
| DYNAMIC ROLLING RADIUS | 722 mm @ 4375 kg / 320 kPa |
| SPEED RADIUS INDEX | 725 |
| TUBELESS VALVE | TR618A |
| BELT MATERIAL | Steel |
| STUDDABLE | Yes Marked stud positions on tread Number of studs 152 pcs |
| VOLUME | 482 l 100% 362 l 75% |

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

| Tire volume 100% | | Water filling 75% | | Water/salt filling (75% / -30°C) | | | | Total weight increase | |
|------------------|---------|-------------------|---------|----------------------------------|---------|------|-----|-----------------------|-----|
| | | | | Water | | Salt | | | |
| Litres | Gallons | Litres | Gallons | Litres | Gallons | kg | lbs | kg | lbs |
| 482 | 127 | 362 | 95 | 297 | 78 | 151 | 333 | 448 | 988 |

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/