

650/45-22.5 175A8 GROUND KARE SF TL

Excavator and backhoe loader tire for versatile contracting work

PRODUCT CODE	T445664
APPLICATION	Wheeled excavator
LI / SPEED SYMBOL	175A8
PLY RATING	24
RIM RECOMMENDED	AG22.00
RIM PERMITTED	AG20.00
TYPE APPROVAL	E8 106R-001143



LOAD CAPACITY FOR WHEELED EXCAVATOR, LB

Constant load

Pressure (psi)	Speed (mph)								
	0	2.5	5	10	12	15	17.5	22.5	25
52	22190	13990	12060	10900	10515	10230	10030	9845	9645
58	24085	15190	13095	11840	11420	11100	10890	10680	10470
65	26875	16945	14605	13205	12730	12390	12145	11915	11685
73	29410	18540	15985	14450	13935	13560	13295	13040	12785
80	31945	20140	17360	15695	15135	14725	14440	14165	13890
87	34985	22055	19015	17185	16580	16125	15820	15520	15210

TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	45.1 in	47.2 in
TIRE WIDTH	26.1 in	27.4 in
PATTERN DEPTH	33/32 in	
MAX. INFLATION PRESSURE	87 psi	

STATIC LOADED RADIUS	20.6 in @ 15200 lb / 87 psi
DYNAMIC ROLLING CIRCUMFERENCE	137.5 in @ 15200 lb / 87 psi
DYNAMIC ROLLING RADIUS	21.9 in @ 15200 lb / 87 psi
SPEED RADIUS INDEX	550
TUBE PRODUCT CODE	T55092
VOLUME	79 gallons 100% 59 gallons 75%

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
300	79	225	59	185	49	94	207	279	615

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/