

420/70R28 144D/141E GROUND KING TL

Combining all-terrain mobility with on-road performance

| | |
|-------------------|----------------|
| PRODUCT CODE | T445733 |
| APPLICATION | Tractor |
| LI / SPEED SYMBOL | 144D (141E) |
| RIM RECOMMENDED | DW13 |
| RIM PERMITTED | DW14L |
| TYPE APPROVAL | E8 106R-001803 |



LOAD CAPACITY FOR TRACTOR, KG

Tractor

| Pressure (kPa) | Speed (km/h) | | | | | | | | | | | | | |
|----------------|--------------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| | 5 | 10 | 15 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70 |
| 80 | 2245 | 1980 | 1770 | 1625 | 1565 | 1520 | 1480 | 1445 | 1410 | 1385 | 1360 | 1340 | 1320 | 1200 |
| 120 | 2890 | 2550 | 2280 | 2090 | 2015 | 1955 | 1905 | 1860 | 1820 | 1785 | 1750 | 1725 | 1700 | 1545 |
| 160 | 3500 | 3090 | 2760 | 2535 | 2440 | 2370 | 2305 | 2255 | 2205 | 2165 | 2120 | 2090 | 2060 | 1875 |
| 200 | 3810 | 3360 | 3000 | 2755 | 2655 | 2575 | 2510 | 2455 | 2395 | 2350 | 2305 | 2275 | 2240 | 2040 |
| 240 | 4130 | 3645 | 3255 | 2990 | 2880 | 2795 | 2720 | 2660 | 2600 | 2550 | 2505 | 2465 | 2430 | 2210 |
| 280 | 4505 | 3975 | 3550 | 3260 | 3140 | 3050 | 2970 | 2900 | 2835 | 2785 | 2730 | 2690 | 2650 | 2410 |
| 320 | 4760 | 4200 | 3750 | 3445 | 3320 | 3220 | 3135 | 3065 | 2995 | 2940 | 2885 | 2840 | 2800 | 2550 |

TIRE DIMENSIONS

| | New tire | Max. in service |
|-------------------------|----------|-----------------|
| OVERALL DIAMETER | 1352 mm | 1375 mm |
| TIRE WIDTH | 408 mm | 439 mm |
| PATTERN DEPTH | 46 mm | |
| MAX. INFLATION PRESSURE | 320 kPa | |

| | |
|-------------------------------|--|
| STATIC LOADED RADIUS | 620 mm @ 2800 kg / 320 kPa |
| DYNAMIC ROLLING CIRCUMFERENCE | 4102 mm @ 2800 kg / 320 kPa |
| DYNAMIC ROLLING RADIUS | 653 mm @ 2800 kg / 320 kPa |
| SPEED RADIUS INDEX | 650 |
| TUBELESS VALVE | TR618A |
| BELT MATERIAL | Steel |
| MARKINGS | M+S |
| STUDDABLE | Yes Marked stud positions on tread Number of studs 144 pcs Recommended stud 12-20,12-23-12-24,16-19 |
| VOLUME | 265 l 100% 199 l 75% |

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

| Tire volume 100% | | Water filling 75% | | Water/salt filling (75% / -30°C) | | | | Total weight increase | |
|------------------|---------|-------------------|---------|----------------------------------|---------|------|-----|-----------------------|-----|
| | | | | Water | | Salt | | | |
| Litres | Gallons | Litres | Gallons | Litres | Gallons | kg | lbs | kg | lbs |
| 265 | 70 | 199 | 53 | 163 | 43 | 83 | 183 | 246 | 542 |

NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

More information: www.nokiantyres.com/heavy/technical-tire-manual/