

NOKIAN CT 560/60R22.5 165D CT TL

PRODUCT CODE	T445626
APPLICATION	Trailer & Implement Front Wheels
PLY RATING / LI / SPEED SYMBOL	165/D
RIM RECOMMENDED	AG16.00
RIM PERMITTED	AG18.00



NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according to the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	1245 mm	
TIRE WIDTH	560 mm	
PATTERN DEPTH	22 mm	

More information: www.nokiantyres.com/heavy/technical-tire-manual/

STATIC LOADED RADIUS	555 mm
DYNAMIC ROLLING CIRCUMFERENCE	3811 mm
DYNAMIC ROLLING RADIUS	1213 mm
VOLUME	390 l

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
390.00	103.03	292.50	77.27	239.99	63.40	122.36	269.75	303.39	668.86