

NOKIAN CT 600/60R30.5 173D CT TL

PRODUCT CODE	T445629
APPLICATION	Trailer & Implement Front Wheels
PLY RATING / LI / SPEED SYMBOL	173/D
RIM RECOMMENDED	AG20.00



NOKIAN TYRES PLC is a full member of ETRTO and affiliated member of TRA. In design and production, we certify that products made in Nokian factory (YL) are according the ETRTO and TRA standards.

Tyre have been manufactured and tested in accordance with the requirements of ISO 9001 and ISO 14001. Nokian Tyres Plc has the following certificates:

- Quality Management System Standard, ISO 9001, Certificate No: 76363-2010-AQ-FIN-FINAS
- Environmental Management System Standard, ISO 14001, Certificate No: 76361-2010-AE-FIN-FINAS

TIRE DIMENSIONS

	New tire	Max. in service
OVERALL DIAMETER	1496 mm	
TIRE WIDTH	607 mm	
PATTERN DEPTH	26 mm	

More information: www.nokiantyres.com/heavy/technical-tire-manual/

STATIC LOADED RADIUS	681 mm
DYNAMIC ROLLING CIRCUMFERENCE	4570 mm
DYNAMIC ROLLING RADIUS	1455 mm
VOLUME	560 l

WATER AND SALT BALLASTING

(CaCl₂, 75%, -30°C) Always use a tube when filled with water/salt.

Tire volume 100%		Water filling 75%		Water/salt filling (75% / -30°C)				Total weight increase	
				Water		Salt			
Litres	Gallons	Litres	Gallons	Litres	Gallons	kg	lbs	kg	lbs
560.00	147.94	420.00	110.95	344.61	91.04	175.69	387.33	435.64	960.42